



TYP PFN

PREFILTERS OR FINAL FILTERS IN VENTILATION SYSTEMS

Pocket filters for the separation of fine dust

- Filter classes M6, F7, F9
- Performance data tested to EN 779
- Eurovent certification for fine dust filters
- Meets the hygiene requirements of VDI 6022
- High energy efficiency according to Eurovent
- NanoWave® medium, sewn
- Enlarged filter area due to filter pockets Different numbers of pockets and pocket depths
- NanoWave® medium with extremely low initial differential pressure and highest possible dust holding capacity, ideal airflow conditions due to trapezoidal filter pockets
- Quick installation and filter changing times due to easy, safe handling
- Fitting into standard cell frames for filter walls (type SIF) or into universal casings (type UCA) for duct installation

Optional equipment and accessories

- Front frame made of plastic or galvanised sheet steel

Application

Application

- Pocket filter made of NanoWave® medium type PFN for the separation of fine dust
- Fine dust filter: Prefilter or final filter in ventilation systems

Description

Filter classes

- Fine dust filters M6, F7, F9

Construction

- PLA: Frame made of plastic
- GAL: Frame made of galvanised steel

Useful additions

- Filter wall (SIF)
- Universal casing (UCA)

Construction features

- Wedge-shaped filter pockets
- Multi-layer filter medium with a prefilter layer and a layer of corrugated extra fine fibres
- Frame depth of construction PLA: 25 mm
- Frame depth of construction GAL: 20, 25 mm
- Number of pockets: 3, 4, 5, 6, 7, 8, 10

Materials and surfaces

- Filter media made of synthetic fibres
- Frame made of plastic or galvanised sheet steel

INFORMACJE TECHNICZNE

Filter class according to EN 779	M6	F7	F9
Average arrestance according to EN 779	>98 %	>98 %	>98 %
Average efficiency according to EN 779	65 %	85 %	>95 %
Initial differential pressure at nominal volume flow rate	60 Pa	80 Pa	130 Pa
Recommended final differential pressure	250 – 350 Pa	250 – 350 Pa	250 – 350 Pa
Max. operating temperature for frames made of plastic	60°C	60°C	60°C
Max. operating temperature for frames made of galvanised sheet steel	90°C	90°C	90°C

Pocket filter PFN made of NanoWave® medium as prefilters or final filters for the separation of fine dust in ventilation systems.

Wedge-shaped filter pockets ensure ideal airflow conditions.

Highest possible dust holding capacity with an extremely low initial differential pressure due to a multi-layer filter medium with a prefilter layer and a layer of corrugated extra fine fibres.

Pocket filters made of NanoWave® medium are available in standard sizes; variable number of pockets and pocket depth; filter classes M6, F7, F9.

Pocket filters made of NanoWave® medium are certified by Eurovent and meet the hygiene requirements of VDI 6022.

Materials and surfaces

- Filter media made of synthetic fibres
- Frame made of plastic or galvanised sheet steel

Construction

- PLA: Frame made of plastic
- GAL: Frame made of galvanised steel

Sizing data

- Filter class
- Volume flow rate [m³/h]
- Initial differential pressure [Pa]
- Nominal size [mm]

PFN

PFN – F7 – PLA – 25 / 592 x 592 x 600 x 8					
1	2	3	4	5	6

1 Type

PFN Pocket filters made of NanoWave® medium

4 Frame depth [mm]

20 (Only with GAL)
25

2 Filter class

M6 Fine dust filter according to EN 779
F7 Fine dust filter according to EN 779
F9 Fine dust filter according to EN 779

5 Nominal size [mm]

B x H x T

3 Construction

PLA Frame made of plastic
GAL Frame made of galvanised steel

6 Number of pockets

3
4
5
6
7
8
10

TROX BSH Technik Polska Sp. z o.o.



TROX BSH Technik Polska Sp. z o.o.
ul.Kolejowa 13, Stara Iwiczna
05-500 Piaseczno
telefon +48 22 737 18 58
e-mail: biuro@trox-bsh.pl

Kontakt online

› [Zgłoszenie usterki](#)

Formularz kontaktowy

TROX BSH Stara Iwiczna

Telefon: +48 22 73718 58

[Kontakt](#)

TROX w serwisach społecznościowych
