



## TYP VME

### FOR THE MEASUREMENT OF VOLUME FLOW RATES IN DUCTS

Rectangular volume flow rate measuring units for the recording or monitoring of volume flow rates

- Manual volume flow rate measuring
- Permanent volume flow rate measuring
- Recording of measured values and use for slave controllers
- Suitable for airflow velocities of up to 10 m/s
- Pressure transducer for the automatic recording of measured values, factory-assembled and complete with wiring and tubing
- Casing air leakage to EN 15727, class C

## Application

### Application

- Rectangular volume flow rate measuring units Type VME for the manual recording or automatic measuring of volume flow rates
- Simplified commissioning, approval and maintenance
- Suitable for permanent installation because of low differential pressure

### Special features

- Measurement accuracy  $\pm 5\%$  even with unfavourable upstream conditions
- Effective pressure range: approx. 8 – 200 Pa
- Low differential pressure of only about 17 – 32 % of the measured effective pressure

## Description

### Construction

- Galvanised sheet steel
- P1: Powder-coated, silver grey (RAL 7001)

### Parts and characteristics

- Ready-to-commission unit which consists of the mechanical parts and an optional pressure transducer
- Averaging differential pressure sensor for volume flow rate measurement
- Optional factory-assembled pressure transducers complete with wiring and tubing
- High measurement accuracy

### Attachments

- Dynamic differential pressure transducer
- Static differential pressure transducer

### Construction features

- Rectangular casing
- Flanges on both sides, suitable for duct connection

- Connecting nipple for tubes with 6 mm inside diameter

#### Materials and surfaces

- Casing made of galvanised sheet steel
- Aluminium sensor tubes

## INFORMACJE TECHNICZNE

#### Functional description

The measuring unit is fitted with an effective pressure sensor for measuring the volume flow rate.

The effective pressure is either measured and evaluated manually, or transformed into an electric signal by a pressure transducer.

Nominal sizes	200 × 100 – 1000 × 1000
Volume flow rate range	45 – 10100 l/s
Volume flow rate range	162 – 36360 m <sup>3</sup> /h
Measurement accuracy	± 5 % of the measured value
Effective pressure range	approx. 8 – 200 Pa
Differential pressure	17 – 32 % of the measured effective pressure
Operating temperature	10 – 50 °C

Rectangular volume flow rate measuring unit for the measurement of volume flow rates in air conditioning systems, available in 39 nominal sizes.

For the manual volume flow rate measuring or for the permanent monitoring of the actual value signal.

Ready-to-commission unit which consists of the casing with an averaging differential pressure sensor.

Differential pressure sensor with 3 mm measuring holes (resistant to dust and pollution)

Both ends suitable for the connection of air duct profiles.

Casing air leakage to EN 15727, class B.

#### Special features

- Measurement accuracy ± 5 % even with unfavourable upstream conditions
- Effective pressure range: approx. 8 – 200 Pa
- Low differential pressure of only about 17 – 32 % of the measured effective pressure

#### Materials and surfaces

- Casing made of galvanised sheet steel
- Aluminium sensor tubes

#### Construction

- Galvanised sheet steel
- P1: Powder-coated, silver grey (RAL 7001)

#### Technical data


- Nominal sizes: 200 × 100 to 1000 × 1000
- Volume flow rate range: 45 – 10100 l/s or 162 – 36360 m<sup>3</sup>/h
- Differential pressure: 17 – 32 % of the measured effective pressure

#### Attachments

Volume flow rate measurement with dynamic differential pressure transducer with actual value signal for integration into the central BMS.

- Supply voltage 24 V AC/DC
- Signal voltages 0 – 10 V DC or 2 – 10 V DC

VME



**1** Type

**VME** Rectangular volume flow rate measuring unit

**3** Nominal size [mm]

B × H

**2** Material

No entry: galvanised sheet steel

**P1** Powder-coated, silver grey (RAL 7001)

**4** Differential pressure transducer

No entry: none

**B10** Dynamic differential pressure transducer

**BB0** Static differential pressure transducer

TROX BSH Technik Polska Sp. z o.o.

□

TROX BSH Technik Polska Sp. z o.o.  
ul. Kolejowa 13, Stara Iwiczna  
05-500 Piaseczno  
telefon +48 22 737 18 58  
e-mail: [biuro@trox-bsh.pl](mailto:biuro@trox-bsh.pl)

Kontakt online

- > Kontakt
- > Zgłoszenie usterki
- > Zapytanie ofertowe - szafy

Formularz kontaktowy

TROX BSH Stara Iwiczna

Telefon: +48 22 73718 58

[Kontakt](#)

TROX w serwisach społecznościowych